



TYCO MZXE

Tyco MZX-E Extinguishing Control Panel

MZX-E är en kraftfull och användarvänlig kontrollpanel. Designad och tillverkad till en hög standard. Panelen har godkännande enligt BS EN 12094-1: 2003, BS EN 54-2 och 4 och är utformad för BS 7273 del 1.

Panelen har omfattande konfigurationsalternativ men är lätt att installera, programmera och använda. Det avtagbara chassit möjliggör ingenjören att "först fixa" ett tomt skåp och sedan montera chassi vid driftsättning. Detta stöds av omfattande dokumentation om driftsättning, drift, underhåll och felsökning. Dessutom finns det ett omfattande utbud av kompatibla och tillgängliga tillbehör för att möta de flesta kundkrav.

- Comprehensive facilities for gaseous extinguishing systems
- Monitored inputs for gas discharged, gas low, isolation valve closed/abnormal, gas trapped in manifold
- Control inputs for auto/manual, gas hold, gas abort
- 1 minute actuator cut off option
- Monitored actuator/solenoid release
- Extensive disablement options
- Common fire, fault, relay / monitored output facilities
- 1st, 2nd, 3rd stage and gas discharged relay / monitored output facilities
- Reset relay facilities
- Intrinsically safe barrier settings
- Metron or solenoid compatible
- Single or double knock operation
- Pre-discharge delay adjustable from 0 to 60 seconds
- Discharged indication with or without pressure switch
- Inhibit silence alarms until gas discharged
- Latching or non latching fault indication option
- Option for rapid buzzer pulse when gas imminent
- One man zone and sounder test
- Approval to BS EN 12094-1:2003 additional options
- Approval to BS EN 54-2 and 4
- Designed to BS 7273-1:2000
- Easily removable chassis

